


FRAME SCREW L WITH SHARP POINT FOR WOOD AND CONCRETE

AREA OF USE

ESSVE Frame screw L with sharp point is designed for the installation of frames for interior doors in wood, concrete, lightweight concrete, brick and hollow brick. Frame screw L provides for fully adjustable installation.

DESCRIPTION

It is made of hardened steel with bright zinc plated surface treatment. The screw is designed for step-drilled frames and is equipped with TX-drive/bit, TX25. When the frame screw L is driven into the frame, the barbs under the head grip in the frame. The frame is then adjusted by either screwing the Frame screw L inwards or outwards. The installation is then hidden by a plastic cover.




INSTALLATION INSTRUCTIONS

The installation is performed in a single step, tight the Frame screw L in the frame and underlying structure. The barbs under the head are pressed into the 5 mm hole. Installation depth requirement is min. 45 mm in the structure material.

MOUNTING



Installation in concrete
Pre-drill the concrete \varnothing 6.0 mm, drill depth about 40 mm for the ESSVE N-plug 6 x 30.



Installation in wood
Installation in wood can be performed very quickly. The studs do not need to be predrilled. Frame screw L is machine-driven directly into the wooden stud.

Specification

Surface treatment	Zinc plated
Corrosion resistance class	C1

C1

Small Pack

Item no	Diameter	Length	Diameter of head	Type of bits	Packaging	Contents
10003668	6 mm	70 mm	12 mm	TX25	Zip-lock poly bag 12cm	8 PCS
10003666	6 mm	90 mm	12 mm	TX25	Zip-lock poly bag 12cm	8 PCS
10003669	6 mm	110 mm	12 mm	TX25	Zip-lock poly bag 16 cm	8 PCS